



**产品特性/Product Features**

- IP6K9K
- 10A 85°C
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1

**触点参数 / Contact parameters**

		1a	
		4.5mΩ (at 10A)	
		10A	
		2×10 <sup>-5</sup>	
		<b>450V型</b>	<b>750V型</b>
		1000VDC	1000VDC
		100A(320VDC)1	100A(320VDC)1
		4.5kW	7.5kW
1)		1×10 <sup>-5</sup> 450VDC,10A)	1×10 <sup>-5</sup> 750VDC,10A)
	2)	10A:	
		15A:1h	
		20A:20min	
		40A:30s	
		60A:10s	
		100A:0.6s	

1) 23°C, 0.6s:5.4s.

2) 85°C, 2.5 mm², " "

性能参数 / Performance parameters

		1000MΩ(1000VDC)
		3000VAC 1min
		3000VAC 1min
( )		≤30ms
( )		≤10ms
		196m/s <sup>2</sup>
		490m/s <sup>2</sup>
		10Hz ~ 500Hz 49m/s <sup>2</sup>
		5% ~ 85%RH
		-40°C ~ 85°C
		QC
		150g
		66.8mm×39.0mm×48.2mm

线圈参数 / Coil parameters

VDC	VDC	VDC	W
12	9	1	2.6
24	≤18	≥2	2.6

-40°C ~ 85°C)

外形图、安装孔尺寸 / Outline drawing, mounting hole size

10mm ±0.2mm

10-50 mm

2

